

Inlet grille in cast-iron concrete frame

D400 - heavy traffic load

Europa 9



Code	KDA9M
Material	Concrete, Cast iron
Weight	116 kg
Norm	EN124-2
Package	10 ks/pal
Load class	Heavy traffic load

Poklop EUROPA 9 s pantem, víko litina kruhová vtoková mříž s uzavřeným pantem, pružinové zajištění víka v rámu, D400, rám beton-litina v.160mm s osazením pro lapač, horizontální a vertikální PUR tlumicí vložka na víku

COVER:




- | Integrated KASI-PUR damping insert with high resistance
- | Hinge secured against removal from the frame
- | Safety lock at 90°
- | Lid weight 37kg
- | Securing the lid in the frame with multi-point springs

FRAME:

- | Cast-concrete frame with mounting for trap
- | Frame height 160 mm
- | Machined frame contact surface to 0.1mm
- | Use with BAR-V and BAR adjustment rings

OTHER:

- | The cover is supplied without surface treatment - painted variants can be ordered
- | Option of screw locking
- | Suitable for places with high traffic load
- | Lid safety lock at 90°



DAMPING INSERT



MAX. OPENING
ANGLE



ANTI-THEFT
PROTECTION



RAINWATER
DRAINAGE