

## Manhole cover with ventilation in self-levelling frame

E600 - extreme loads

# EUROPA 9



Code	<b>KEM92</b>
Material	<b>Cast iron</b>
Weight	<b>78 kg</b>
Norm	<b>EN124-2</b>
Package	<b>14 ks/pal</b>
Load class	<b>Extreme traffic load</b>

Poklop EUROPA 9 s pantem, víko litina s ventilací s uzavřeným pantem, pružinové zajištění víka v rámu, E600, rám litina samonivelační v.160mm bez osazení pro lapač, horizontální a vertikální PUR tlumící vložka na víku

### COVER:

- | Integrated KASI-PUR damping insert with high resistance
- | Cast iron without ventilation with non-slip design.
- | Hinge secured preventing removal from frame
- | Safety locking at 90°, max. opening 120°
- | Lid weight 47 kg

### FRAME:

- | Self-levelling frame without trap mounting
- | Frame height 160 mm, weight 21 kg
- | Machined bearing surface of the frame to 0.1 mm
- | Use with BAR-V and BAR adjustment rings
- | Installation without guide ring – frame can be inserted directly into well

### OTHER:

- | Hatch comes without coating – painted options can be ordered
- | Option with screw locking
- | Suitable for places with extreme traffic loads
- | Safety locking of the lid at 90°, max. opening 120°

Custom motif or logo possible



CUSTOM SOLUTIONS



DAMPING INSERT



MAX. OPENING ANGLE



THEFT PROTECTION

