

Manhole cover without ventilation in self-levelling frame

E600 - extreme loads

EUROPA 9



Code	KEMH97
Material	Cast iron
Weight	84 kg
Norm	EN124-2
Package	14 ks/pal
Load class	Extreme traffic load

Poklop EUROPA 9 s pantem, víko litina bez ventilace s otevřeným pantem tichý design, pružinové zajištění víka v rámu, E600, rám litina samonivelační těžký v.160mm bez osazení pro lapač, horizontální a vertikální PUR tlumící vložka na víku

COVER:



- | Lid weight 49 kg
- | Lid secured in frame with multi-point springs
- | Integrated KASI-PUR damping insert with high resistance
- | Safety locking at 90°, max. opening 120°
- | Hinge enabling removal from frame

FRAME:

- | Frame height 160 mm, weight 35 kg
- | Use with BAR-V and BAR adjustment rings
- | Installation in the running layer and load transfer outside the well
- | Installation without guide ring – frame can be inserted directly into well
- | Suitable for places with extreme traffic loads

OTHER:

- | Option with screw locking
- | custom motif on the lid possible
- | Hatch comes without coating – painted options can be ordered



CUSTOM SOLUTIONS



DAMPING INSERT



MAX. OPENING ANGLE



QUIET DESIGN

